



7" x 12" horizontal metal cutting bandsaw

Horizontal or vertical cutting. Automatic shutoff. Coolant system with built-in tank and pump. Adjustable hydraulic down feed control. 4 blade speeds: 86, 132, 178 and 260 fpm. 1 HP motor.



metal cutting bandsaw

One-piece heavy-duty thick steel upper frame. Welded one-piece base made of high-quality steel with built-in coolant tank and recovery tray. Adjustable hydraulic down feed control. 4 blade speeds: 82, 132, 170 and 235 fpm. 1 ½ HP motor.

Electronic variable speed drill press

Front mounted digital spindle speed display. Electronic variable speed control adjusts spindle speed from 150 to 3000 rpm. Forward/reverse tapping system. Large base with built-in coolant tank. 2 HP motor.

75-915T M1

reg. \$4,100.00

Distributed by:

11" x 26" Variable speed metal lathe with stand

26" distance between centers. Digital speed display. Pulley case and chuck guard both equipped with auto shut-off safety switch. Low voltage transformer. Full length lead-screw cover / guard for operator safety. Easy change variable speed (50 - 2150 rpm). 2 HP motor.





14" drill press

%" chuck with key, laser line marker & see-through chuck guard included. Rotating, 45° tilting, crank-operated worktable with quick release clamp. Built-in lamp illuminates the drilling area (bulb not included). 12 spindle speeds: 280 to 3000 rpm. ½ HP motor.

16" drill press

%" chuck with key, laser line marker & see-through chuck guard included. Rotating, 45° tilting, crank-operated worktable with quick release clamp. Built-in lamp illuminates the drilling area (bulb not included). 12 spindle speeds: 280 to 3000 rpm. ½ HP motor.

22" drill press

%" chuck with key, laser line marker & see-through chuck guard included. Rotating, 45° tilting, crank-operated worktable with quick release clamp. Built-in lamp illuminates the drilling area (bulb not included). 12 spindle speeds: 120 to 2270 rpm. 1 HP motor.



12" slow speed cold cut saw

Blade speed: 52 rpm - ideal for cutting ferrous materials. Miter stops at 90°, 45° left or right. Coolant pump system with high volume tank. Magnetic switch with overload protection. 2 ½ HP motor. Blade not included.





14" variable speed cold cut saw

Variable blade speed: 24 to 120 rpm - ideal for cutting ferrous materials. Miter stops at 90°, 45° left or right. Coolant pump system with high volume tank. Magnetic switch with overload protection. 3 HP motor. Blade not included.

14" x 120D hi-speed steel blade 60-355 \$244.99 reg. \$360.00



Geared head milling / drilling machine

Head swivels 360° and tilts up to 30° left and 90° right for angle drilling, milling, slotting and more. Magnetic safety switch with forward/reverse controls. 6 spindle speeds: 60, 130, 230, 450, 800 & 1500 rpm. See-through chuck guard with safety interlock and safety limit switches. 1 ½ HP motor.

Optional cabinet stand
75-885
\$239.99
reg. \$350.00



95-400 \$64.99 reg. \$90.00

6" industrial bench vise Heavy-duty casting (45 000 P.S.I.)

95-860 **\$249.99**



70-520 **\$79.99** reg. \$99.00

52 piece clamping kit

Heavy-duty roller stands with 2000 lb load capacity

Heavy-duty cast-iron and steel construction. Chrome-plated ball bearing roller. Adjustable height (23 ½" to

